



G2 SERIES (PRECISION TURBINE METERS)

A full line of FLOMEC® G2 Series Precision Turbine Meters are available in a variety of housing materials. Rugged and dependable, the G2 Series offers:

- Stainless Steel for most chemicals and fuel products
- Aluminum for petroleum based products
- Brass for most water applications
- PVDF for aggressive chemicals

FEATURES / BENEFITS

- Meter is designed for thin fluids < 100 cp
- Modular design allows for use with Output Modules, Sensors and Remote Transmitters
- 2 Totals (Batch = Resettable, Cumulative = Non-resettable); Rate of Flow, Factory calibrated in gallons and litres. Field calibratable. Includes non-volatile totals.
- High accuracy meter
- Internal parts are simple to replace for easy maintenance
- Lithium battery life: 5 years

APPLICATIONS

- | | |
|---------------------|---|
| • Batching | • Food & Beverage Processing |
| • Blending | • Fuel Products |
| • Water | • Monitoring Clean Fluids |
| • Industrial Fluids | • Plant Process Water |
| • Plating Solutions | • Chemical Feed Lines |
| • Ammonium | • Harsh Chemicals
(Sulfuric Acid & Bleach) |

PRODUCT CONFIGURATION

PRODUCT IDENTIFIER 1

G2 = Industrial Grade Flowmeter

TURBINE MATERIAL 2

S = Stainless Steel
A = Aluminum
P = PVDF (1/2" & 1" only)
H = High Pressure Stainless Steel
B = Brass

TURBINE SIZE 3

05 = 1/2 inch
07 = 3/4 inch
10 = 1 inch
15 = 1-1/2 inch
20 = 2 inch

FITTING TYPE 4

I = ISO (Female) BSPT (ISO 7 Designation is RC)
N = NPT (Female)
F = 150# ANSI Flange - available on S10, S15 and S20 only
T = Tri-Clover® fitting - available on S05-S20 only
X = Electronics only - for metal meters
Z = Electronics only - for plastic meters

ELECTRONIC CHOICE 5

Turbine with Local Display

09 = 2-Button Computer, Field Configurable (Cumulative, Batch & Rate)

19 = Vertical Mount 2-Button Computer, Field Configurable (Cumulative, Batch & Rate)

No Electronics - Turbine Only

XX = No Electronics - Turbine Only

CALIBRATION 6

GM = GPM & L/min (Gallons Default)

LM = GPM & L/min (Litres Default)

XX = No Calibration (Use with Electronic Choices 41, 71, 72 or Turbine Only)

PACKAGING 7

A = Use for Turbine Only or 09 Electronics choice (Sizes 05-10)

B = Use for Turbine Only or 09 Electronics choice (Sizes 15-20)

Use for 19 Electronics choice (Sizes 05-10)

C = Use for 19 Electronics choice (Sizes 15-20)

1 2 3 4 5 6 7
 --->>>> G2 S 15 N 09 GM B

SPECIFICATIONS

Fitting Type:	NPT or ISO (Female) BSPT* (*ISO 7 designation is RC)		
	150# ANSI (Stainless Steel only)		
	Tri-Clover® (Stainless Steel only) - Clamp size is one size bigger than meter size		
Housing Material:	316 Stainless Steel, Aluminum, Brass, PVDF		
Meter Sizes Available:	1/2" 3/4" 1" 1-1/2" 2"		
Flow Range:	1/2" (05)	1 - 10 GPM	(3.8 - 38 L/min)
	1/2" (05) <i>PVDF only</i>	1.2 - 12 GPM	(4.5 - 45 L/min)
	3/4" (07)	2 - 20 GPM	(7.6 - 76 L/min)
	1" (10)	5 - 50 GPM	(19 - 190 L/min)
	1-1/2" (15)	10 - 100 GPM	(38 - 380 L/min)
	2" (20)	20 - 200 GPM	(76 - 760 L/min)
Accuracy (% of Reading):	Turbine Only		Turbine w/Computer
	1/2" (05)	± 2.0%	± 1.5%
	3/4" (07)	± 1.5%	± 1.0%
	1" (10)	± 1.5%	± 1.0%
	1-1/2" (15)	± 1.0%	± 0.75%
	2" (20)	± 1.0%	± 0.75%
Repeatability:	± 0.1% (PVDF is ± 0.3%)		
Pressure Rating:			
316 Stainless Steel	1,500 psi (102 bar)		
Aluminum	300 psi (21 bar)		
Brass	300 psi (21 bar)		
High Pressure 316 Stainless Steel	3000 psi (207 bar) (CE Approval ONLY)		
ANSI Flange 316 Stainless Steel	Flange Rule		
Sanitary Flange 316 Stainless Steel	Limited by fitting size, clamp size & temperature		
PVDF	100 psi (6.9 bar)		


Operating Temperature Range:	-40° F to 250° F (-40° C to 121° C)	
	(PVDF) -20° F to 180° F (-28° C to 82° C)	
with Display:	14° F to 140° F (-10° C to 60° C)	
Typical K-Factor:	1/2" (05)	2,500 PPG (660 Pulses/L)
	3/4" (07)	1,100 PPG (291 Pulses/L)
	1" (10)	565 PPG (149 Pulses/L)
	1-1/2" (15)	215 PPG (57 Pulses/L)
	2" (20)	100 PPG (26 Pulses/L)
	Wetted Materials:	Housing:
Bearings:		96% Alumina Ceramic
Shaft:		Tungsten Carbide
Rotor:		PVDF
Rings:		316 Stainless Steel
Wetted Materials PVDF:	Housing:	PVDF (15% Carbon Fiber Filled)
	Bearings & Shaft:	98% Alumina Ceramic
	Rotor:	PVDF
	Rings:	Fluorocarbon (Optional PTFE)
Frequency Range:	1/2" (05)	42-420 Hz @ 1-10 GPM (3.8-38 L/min) / 48-480 Hz @ 1.2-12 GPM (4.5-45 L/min) (PVDF)
	3/4" (07)	37-370 Hz @ 2-20 GPM (7.6-76 L/min)
	1" (10)	47-470 Hz @ 5-50 GPM (19-190 L/min) / 45-450 Hz @ 5-50 GPM (19-190 L/min) (PVDF)
	1-1/2" (15)	36-360 Hz @ 10-100 GPM (38-380 L/min)
	2" (20)	33-330 Hz @ 20-200 GPM (76-760 L/min)
	Calibration Report:	Comes standard with G2 Series meters.
N.I.S.T. - Certification available.		

DIMENSIONS

NOTE: 09 Display adds 0.67 in. (17 mm) to height.

NPT/ISO

Meter Size	Length " (mm)	Height " (mm)	Width " (mm)	Meter Size	Length " (mm)	Height " (mm)	Width " (mm)
1/2"	4.2 (107)	1.8 (46)	2.0 (51)	2"	6.3 (160)	3.2 (81)	3.3 (84)
3/4"	4.3 (109)	2.0 (51)	2.0 (51)	PVDF 1/2"	7.3 (185)	3.2 (81)	2.1 (53)
1"	4.5 (114)	2.2 (56)	2.0 (51)	PVDF 1"	8.1 (206)	3.3 (84)	2.8 (71)
1-1/2"	5.3 (135)	2.8 (71)	2.7 (68)				



APPROVALS

IP65

NEMA 4

ACCESSORIES / ELECTRONICS

Part No.	Description
113435-1	Conditioned Signal Module
125060-1	Pulse Access Module
125070-1	External Power Module
125100-1	4-20 mA Module
120077-01	FM Approved Sensor
120077-02	ATEX Approved Sensor
125260-01	90 Degree Display Adaptor Kit
113275-1	FM Approved Remote Kit

Part No.	Description
145505-01	Kit, Adapter, G2-QS11-Q09 Display
145505-02	Kit, Adapter, G2-QS12-Q09 Display
145505-03	Kit, Adapter, G2-QS13-Q09 Display
145505-04	Kit, Adapter, G2-QS11-No Display
145505-05	Kit, Adapter, G2-QS12-No Display
145505-06	Kit, Adapter, G2-QS13-No Display
145505-07	Kit, Adapter, G2-QS11-Display Ready
145505-08	Kit, Adapter, G2-QS12-Display Ready
145505-09	Kit, Adapter, G2-QS13-Display Ready

Wichita · Sydney · Mexico City

GREAT PLAINS INDUSTRIES

© 2017 Great Plains Industries, Inc. All Rights Reserved.

Service & Warranty: For technical assistance, warranty replacement or repair contact your **FLOMEC®** or **GPI®** distributor. In North or South America: **888-996-3837 / FLOMEC.net** Outside North or South America: **+61 2 9540 4433 / FLOMEC.net**

01/18 IND-1043-G2